



5 / 8 Ports Gigabit Switch

All Ports Support Auto MDI / MDI-X

ES-5X00S

Taiwan / Headquarters
Edimax Technology Co., LTD.
TEL:886-2-7739-6888
FAX:886-2-7739-6887
sales@edimax.com.tw

China
Beijing Edimax Science &
Technology Co., LTD.
TEL:8610-6213-9288
FAX:8610-6213-9231
sales@edimax.com.cn

U.S.A.
Edimax Computer Company
TEL:1-408-496-1105
FAX:1-408-980-1530
sales@edimax.com

Latin America
TEL:1-786-845-8099
FAX:1-786-331-8490
sales_latinameica@edimax.com

Europe
Edimax Technology Europe B.V.
TEL:31-499-377344
FAX:31-499-372647
sales@edimax.nl

U.K.
Edimax Technology (UK) Ltd.
TEL:44-870-7740226
FAX:44-870-7740227
info@edimax.co.uk



ES-5X00S meets the demand for bandwidth as 5/8 port Desktop Gigabit switch. This desktop switch seamlessly integrates with the rest of the network through its auto-negotiating, non-blocking design. To break through the bottlenecks at the core of network, ES-5X00S provides up to 10Gbps aggregate bandwidth and seamless migration and the most cost effect method for bringing high speed networking to the desktop

- Conforms to IEEE 802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T and IEEE 802.3x flow control standards
- Supports 10/100Mbps auto-detect Half/Full duplex and 1000Mbps at full duplex
- Supports TP interface auto MDI/MDI-X function for auto TX/RX swap
- Supports 802.3x flow control pause packet for full duplex
- LEDs to indicate: 10/100/1000Mbps, Link/Act. and Power Status

Model NO.	ES-5500S	ES-5800S
Standards	IEEE-802.3, IEEE-802.3u, IEEE-802.3ab	
Gigabit Port	5	8
MAC Address	8K	
Buffer Memory	112K	144K
Dimension	27(H) x 159(W) x 102(D) mm	
Weight	450g	
Temperature	0~50 Degree C	
Humidity	0~90% (Non-Condensing)	
Certification	FCC Class A, CE Mark	