



16 / 24 Ports Gigabit Switch Web Smart with 2 x SFP Module Ports

ES-516G+
ES-524G+

Feature

- 16 / 24 x 10/100/1000Mbps Auto-negotiation Gigabit Ethernet TP ports
- 2x 10/100/1000Mbps TP or 1000Mbps SFP Fiber dual media auto sense
- Supports 400KB frame buffer
- Supports 8K MAC address entries
- Full duplex flow control (IEEE802.3x) and half duplex back pressure
- Extensive front-panel diagnostic LEDs; System: Power, Link/Act, 10/100/1000Mbps
- Standard 19" Rack-mount size
- Support 2 fans
- Supports jumbo frame
- Supports port setting function: port enable/disable, speed, duplex mode, and flow control selectable

SFP Optional Modules

- MO-LCM-850** Multi-Mode 850nm (220m or 550m)
- MO-LCS-1310** Single Mode 1310nm, 10Km
- MO-LCS-1550** Single Mode 1550nm, 30Km
- MO-LCB-1310** BiDi Single Mode 1310nm, 20Km
- MO-LCB-1550** BiDi Single Mode 1550nm, 20Km

Taiwan / Headquarters
Edimax Technology Co., LTD.
TEL:886-2-7739-6888
FAX:886-2-7739-6887
sales@edimax.com.tw

China
Beijing Edimax Science &
Technology Co., LTD.
TEL:8610-6213-9288
FAX:8610-6213-9231
sales@edimax.com.cn

U.S.A.
Edimax Computer Company
TEL:1-408-496-1105
FAX:1-408-980-1530
sales@edimax.com

Latin America
TEL:1-786-845-8099
FAX:1-786-331-8490
sales_latinamerica@edimax.com

Europe
Edimax Technology Europe B.V.
TEL:31-499-377344
FAX:31-499-372647
sales@edimax.nl

U.K.
Edimax Technology (UK) Ltd.
TEL:44-870-7740226
FAX:44-870-7740227
info@edimax.co.uk



Model NO.	ES-516G+	ES-524G+
Standards	IEEE-802.3, IEEE-802.3u, IEEE-802.3ab	
Gigabit Port	16	24
MAC Address	8K	
Buffer Memory	400K	400K
Dimension	44(H) x 442(W) x 209(D) mm	
Weight	4.2kgs	
Temperature	0~50 Degree C	
Humidity	5~90% (Non-Condensing)	
Certification	FCC Class A, CE Mark	